465N-8810-0081 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF5 DF4 DF3 DF2 DF1 PF1 PF2 PF3 PF4 PF5
DC PC

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION
		FRONT / CORNER STROBES
0	NONE	NONE
1	ORG & BLU	DF2, PF1 & PF3 SIMULTANEOUS AND ALTERNATE WITH DF3, DF1 & PF2 SIMULTANEOUS DF5 & PF5 SIMULTANEOUS AND ALTERNATE WITH DF4 & PF4 SIMUTANEOUS
2	ORG & BLU & WHT/BLK (w/ PREEMPTION OPTION)	SAME AS MODE 1 – EXCEPT PREEMPTION SIGNAL IS EMITTED

CONTROL WIRES FOR AMBER ICC MARKER LIGHTS

CONTROL WIRE ACTIVATED	HALOGEN LAMP
BRN/WHT	ALL 5 AMBER ICC LIGHTS

CONTROL WIRES FOR HALOGEN CORNER LAMPS

CONTROL WIRE ACTIVATED	HALOGEN LAMP
GRY	DC 45-DEGREE CORNER
YEL	PC 45-DEGREE CORNER

CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP
RED/WHT	PF1 & DF1 SPLIT TAKEDOWN

NOTE: GREEN control wire activates high intensity to strobes.
Apply +12vdc to appropriate control wire to activate desired function.