465N-8810 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF5 DF4 DF3 DF2 DF1 PF1 PF2 PF3 PF4 PF5
DC PC

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION
		FRONT / CORNER STROBES
1	ORG	DF1 ALTERNATES WITH PF1
2	ORG & BLU	DF3, DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1, PF1 & PF3 SIMULTANEOUS DF5 & PF5 SIMULTANEOUS AND ALTERNATE WITH DF4 & PF4 SIMUTANEOUS
3	ORG & BLU & WHT/BLK (PREEMPTION) SEE NOTE*	DF3, DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1, PF1 & PF3 SIMULTANEOUS DF5 & PF5 SIMULTANEOUS AND ALTERNATE WITH DF4 & PF4 SIMUTANEOUS DC ALTERNATES WITH PC

* PREEMPTION SIGNAL IN MODE 3 – ONLY IF PRE OPTION IS ORDERED

CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP	
BROWN	DF1 & PF1	SPLIT TAKEDOWN or SPLIT FRONT FLASHER

CONTROL WIRE FOR OPTIONAL 930-PRE PREEMPTION

CONTROL WIRE ACTIVATED	STROBE LAMP
BRN/WHT	PARKING BRAKE OVERRIDE – MODE 3 - NON-PREEMPTION

NOTE: GREEN control wire activates high intensity to strobes.
Apply +12vdc to appropriate control wire to activate desired function.