

465NH-7208 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF4 DF3 DF2 DF1 PF1 PF2 PF3 PF4
DCPC

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION
		FRONT / CORNER STROBES
1	ORG	DF4 & DF2 SIMULTANEOUS AND ALTERNATE WITH PF4 & PF2 SIMULTANEOUS
2	ORG & BLU	DF4, DF3, DF2 & DF1 SIMULTANEOUS AND ALTERNATE WITH PF4, PF3, PF2 & PF1 SIMULTANEOUS
3	ORG & BLU & WHT/BLK	DF4, DF3, DF2, DF1 & PC SIMULTANEOUS AND ALTERNATE WITH PF4, PF3, PF2, PF1 & DC SIMULTANEOUS
4	BLU (STROBES ONLY)	DF4, DF3, & DF1 SIMULTANEOUS AND ALTERNATE WITH PF4, PF3, & PF1 SIMULTANEOUS
5	WHT/BLK (HALOGENS ONLY MODE 1)	DF2 ALTERNATES WITH PF2
6	ORG & WHT/BLK (HALOGENS ONLY MODE 2)	DF2 & PC SIMULTANEOUS AND ALTERNATE WITH PF2 & DC SIMULTANEOUS

* Note: **OPTIONAL SYNCHRONIZED HALOGENS** – One pair, **DF4 & PF4** or **DF3 & PF3** are optional synchronized halogens - replacing the standard strobe lamps in these locations. When ordered – All mode operation remains the same – However note the Strobe Lamps in Mode 4 (Strobes Only) will now be Halogen and will be activated in Mode 6 (Halogen Only).

CONTROL WIRES FOR OPTIONAL HALOGEN

CONTROL WIRE ACTIVATED	OPERATION
RED/WHITE	DF1 & PF1 SPLIT TAKEDOWN
GRAY	DF3 SPLIT TAKEDOWN
YELLOW	PF3 SPLIT TAKEDOWN

CONTROL WIRES FOR OPTIONAL PRE2-1C

CONTROL WIRE ACTIVATED	DESIGNATED STROBE LAMP
BRN	ACTIVATE PREEMPTION EMITTER

CONTROL WIRES FOR OPTIONAL ICC MARKER LIGHTS

CONTROL WIRE ACTIVATED	ACTIVATE ICC MARKER LIGHTS
BRN/WHT	

**NOTE: GREEN control wire activates high intensity to strobes.
Apply +12vdc to appropriate control wire to activate desired function.**