

930H-4805-0078 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF2	DF1	FC	PF1	PF2
DC				PC
DA				PA
DR2	DR1	RC	PR1	PR2

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR / ALLEY HALOGEN	FRONT / CORNER HALOGEN
0	NONE	NONE	NONE
1	ORG (REAR ONLY)	DR2, PR2 & DA SIMULTANEOUS AND ALTERNATE WITH DR1, PR1 & PA SIMULTANEOUS	NONE
2	ORG & BLU (FRONT ONLY)	NONE	DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1 & PF1 SIMULTANEOUS DC ALTERNATES WITH PC
3	ORG & BLU & WHT/BLK (360 +)	SAME AS MODE 1	SAME AS MODE 2
RIGHT ARROW	BLU	DR2, DR2 & DR1, DR1 & PR1, PR1 & PR2, PR2, DA & PA, REPEAT	DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1 & PF1 SIMULTANEOUS
LEFT ARROW	WHT/BLK	PR2, PR2 & PR1, PR1 & DR1, DR1 & DR2, DR2, DA & PA, REPEAT	DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1 & PF1 SIMULTANEOUS
CENTER OUT	BLU & WHT/BLK	DR1 & PR1, DR2 & DR1 & PR1 & PR2, DR2 & PR2, DA & PA, REPEAT	DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1 & PF1 SIMULTANEOUS

CONTROL WIRES FOR OPTIONAL STEADYBURN HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP
RED/WHITE	RC (REAR WORK)
BROWN	FC (TAKEDOWN)
GRAY	DA (DRIVER ALLEY)
YELLOW	PA (PASSENGER ALLEY)
BRN/WHT	DF1 & PF1 (SPLIT TAKEDOWNS)

NOTE: Apply +12vdc to appropriate control wire to activate desired function.

SPECIAL FEATURE: To disable the Front/Corner Flashing Halogens Lamps in the Directional Modes – short pins 5 & 6 on the 930H-12-0078 Halogen Controller.