

930H-4805-0099 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF2	DF1	FC	PF1	PF2
DC				PC
DAF				PAF
DAR				PAR
DR2	DR1	RC	PR1	PR2

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR / ALLEY HALOGENS	FRONT / CORNER HALOGENS
ALL ON HALOGENS	ORANGE	DAR, DR2, PR2 & PAR SIMULTANEOUS AND ALTERNATE @ 490 ms WITH DAF*, RC & PAF* SIMULTANEOUS DR1 & PR1 ALTERNATE @ 245 ms	DC, DF2, FC, PF2 & PC SIMULTANEOUS AND ALTERNATE @ 490 ms WITH DF1 & PF1 SIMULTANEOUS

***Note: DAF & PAF will flash in the pattern indicated above – until the steadyburn function is activated by control wires indicated below.**

CONTROL WIRES FOR DUAL MODE HALOGEN OVERRIDE

CONTROL WIRE ACTIVATED	HALOGEN LAMP	
GREEN	DAF	STEADYBURN
WHT/BLK	PAF	STEADYBURN

CONTROL WIRES FOR OPTIONAL 2 STROBES

CONTROL WIRE ACTIVATED	STROBE LAMPS - DR1 & PR1
RED/WHT	ACTIVATE STROBES
GRY	ACTIVATE HIGH INTENSITY

NOTE: Apply +12vdc to appropriate control wire to activate desired function.