930H-4805 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF2 DF1 FC PF1 PF2
DC PC
DA PA
DR2 DR1 RC PR1 PR2

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR / ALLEY HALOGENS	FRONT / CORNER HALOGENS
0	NONE	NONE	NONE
FACTORY DEFAULT (INBOARD/OUTBOARD)	ORANGE (WIRED TO PIN 2 OF 930H-16)	DR2, PR2 & DA SIMULTANEOUS AND ALTERNATE WITH DR1, PR1 & PA SIMULTANEOUS	DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1 & PF1 SIMULTANEOUS DC ALTERNATES WITH PC
ALTERNATE PATTERN 1 (LEFT/RIGHT)	ORANGE (WIRED TO PIN 6 OF 930H-16)	DR2, DR1 & DA SIMULTANEOUS AND ALTERNATE WITH PR2, PR1 & PA SIMULTANEOUS	DF2 & DF1 SIMULTANEOUS AND ALTERNATE WITH PF2 & PF1 SIMULTANEOUS DC ALTERNATES WITH PC
ALTERNATE PATTERN 2 (SWEEP)	ORANGE (WIRED TO PIN 7 OF 930H-16)	DR2, DR1, PR1, PR2, PR1, DR1, REPEAT DA ALTERNATES WITH PA	DF2, DF1, PF1, PF2, PF1, DF1, REPEAT DC ALTERNATES WITH PC

CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP	
BLUE	FC	(TAKEDOWN)
WHITE/BLACK	DA & PA	(ALLEYS)
GREEN	RC	(REAR WORK)

CONTROL WIRES FOR OPTIONAL 2 STROBES

CONTROL WIRE ACTIVATED	**STROBE LAMPS** - DR1 & PR1
GRY	ACTIVATE STROBES
BRN/WHT	ACTIVATE HIGH INTENSITY

NOTE: The 930H-4805 lightbar comes wired for the FACTORY DEFAULT flash pattern. This flash pattern alternates the INBOARD halogens with the OUTBOARD halogens. The lightbar may be field selected to operate in one of two alternate flash patterns. The ALTERNATE PATTERN 1 alternates the LEFT (driver's) side halogens with the RIGHT (passenger's) side halogens. To field select this pattern move the ORANGE control wire on the 930H-16 HALOGEN CONTROLLER from pin 2 of the terminal block to pin 6. The ALTERNATE PATTERN 2 operates the front and rear halogens in a SWEEP pattern. To field select this pattern move the ORANGE control wire on the 930H-16 HALOGEN CONTROLLER from pin 2 of the terminal block to pin 7.