930H-6407 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF3 DF2 DF1 FC PF1 PF2 PF3
DC PC
DA PA
DR3 DR2 DR1 RC PR1 PR2 PR3

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		FRONT / CORNER HALOGENS	REAR / ALLEY HALOGENS
INBOARD / OUTBOARD	ORANGE Or ORG & BLU Or ORG & BLU & WHT/BLK	DF3, DF2L, PF2R & PF3 ALTERNATE @ 490 ms WITH DF2R, DF1, PF1 & PF2L DC ALTERNATES WITH PC @ 245 ms	DR3, DR2L, PR2R, PR3 & DA ALTERNATE @ 490 ms WITH DR2R, DR1, PR1, PR2L & PA
PASSENGER / DRIVER SIDES ALTERNATE	BLU Or BLU & WHT/BLK	DF3, DF2 & DF1 ALTERNATE @ 490 ms WITH PF3, PF2 & PF1 DC ALTERNATES WITH PC @ 245 ms	DR3, DR2, DR1 & DA ALTERNATE @ 490 ms WITH PR3, PR2, PR1 & PA
SWEEP	WHT/BLK	DF3 & DF2L, DF2R & DF1, PF1 & PF2L, PF2R & PF3 REPEAT DC ALTERNATES WITH PC @ 196 ms	DR3 & DR2L, DR2R & DR1, PR1 & PR2L, PR2R & PR3 REPEAT PA ALTERNATES WITH DA @ 196 ms

CONTROL WIRES FOR STEADYBURN HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP	
BRN	FC	TAKEDOWN
YEL	DA & PA	ALLEYS
RED/WHT	RC	REAR WORK