

Appendix A

930L-1701 FLASH PATTERNS (VER 02)

FRONT WARNING LAMP (FC):

- 1) OFF
- 2) FAST ALTERNATING
- 3) **SLOW ALTERNATING (FACTORY DEFAULT)**

REAR WARNING LAMP (RC):

- 1) OFF
- 2) FAST ALTERNATING
- 2) **SLOW ALTERNATING (FACTORY DEFAULT)**

CORNER & END WARNING LAMP PATTERNS (DA, PA, DC, PC):

- 1) OFF
- 2) ALLEYS ONLY FAST
- 3) ALLEYS ONLY SLOW
- 4) ALLEYS ALTERNATING FAST
- 5) ALLEYS ALTERNATING SLOW
- 6) CORNERS ONLY FAST
- 7) CORNERS ONLY SLOW
- 8) ALLEYS AND CORNERS FAST
- 9) ALLEYS AND CORNERS SLOW
- 10) ALLEYS ALTERNATING AND CORNERS FAST
- 11) **ALLEYS ALTERNATING AND CORNERS SLOW (FACTORY DEFAULT)**

FLASH RATES:

- 1) **SINGLE FLASH (FACTORY DEFAULT)**
- 2) DOUBLE FLASH
- 3) NEOBE® FLASH (FACTORY DEFAULT)
- 4) SCROLL FLASH (4 SECONDS EACH OF ALL RATES)

NOTE: Each section of the lightbar can operate at different flash rates at the same time and the lightbar can operate different flash rates in each mode.

930L-1701 POWER WIRES

Red	+12 Vdc Power
Black	GROUND

OPTIONAL HALOGEN CONTROL CABLE

Red	Split HL Rearwork or Solid 37HWB - RC
Red/Wht	Split HL Takedown or Solid 37HWB - FC
Black	Split HL Drivers Alley - DA
Yellow	Split HL Passenger Alley - PA