

930N-4805-0012 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

	DF2	DF1	FC	PF1	PF2
DC					PC
DA					PA
	DR2	DR1	RC	PR1	PR2

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR / ALLEY STROBES	FRONT / CORNER STROBES
0	NONE	NONE	NONE
1	ORG	DR2, DR1 & DA SIMULTANEOUS AND ALTERNATE WITH PR2, PR1 & PA SIMULTANEOUS	NONE
2	ORG & BLU	DR2, PR2 & DA SIMULTANEOUS AND ALTERNATE WITH DR1, PR1 & PA SIMULTANEOUS	DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1 & PF1 SIMULTANEOUS
3	ORG & BLU & WHT/BLK	DR2, DR1, PR1, PR2, PR1, DR1, REPEAT (SWEEP) DA ALTERNATES WITH PA	DF2, DF1, PF1, PF2, PF1, DF1, REPEAT (SWEEP) DC ALTERNATES WITH PC
RIGHT ARROW	BLU	DR2, DR2 & DR1, DR1 & PR1, PR1 & PR2, PR2, DA & PA, REPEAT	DF2 ALTERNATES WITH PF2
LEFT ARROW	WHT/BLK	PR2, PR2 & PR1, PR1 & DR1, DR1 & DR2, DR2, DA & PA, REPEAT	DF2 ALTERNATES WITH PF2
CENTER OUT	BLU & WHT/BLK	DR1 & PR1, DR2 & DR1 & PR1 & PR2, DR2 & PR2, DA & PA, REPEAT	DF2 ALTERNATES WITH PF2

CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP
RED/WHITE	RC (REAR WORK)
BROWN	FC (TAKEDOWN)
GRAY	DA (DRIVER ALLEY)
YELLOW	PA (PASSENGER ALLEY)

NOTE: GREEN control wire activates high intensity to strobes.
Apply +12vdc to appropriate control wire to activate desired function.
Cut loop (22 AWG BLACK) on 930F-0012 (FRONT power supply) to disable FRONT strobes during traffic direction modes.