930N-4805-0020 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF2 DF1 FC PF1 PF2
DC PC
DA PA
DR2 DR1 RC PR1 PR2

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR / ALLEY STROBES & HALOGENS	FRONT / CORNER STROBES
0	NONE	NONE	NONE
1	RED/WHT	DR1 ALTERNATES WITH PR1	NONE
2	RED/WHT & BLU	DR2, PR2 & DA SIMULTANEOUS AND ALTERNATE WITH RC & PA SIMULTANEOUS DR1 ALTERNATES WITH PR1	NONE
3	RED/WHT & BLU & WHT/BLK	SAME AS MODE 2	DF1 & PF1 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMULTANEOUS (6 PULSES PER BURST) DC ALTERNATES WITH PC (3 PULSES PER BURST)
REAR STROBES ONLY	BLU	DR2, PR2 & DA SIMULTANEOUS AND ALTERNATE WITH RC & PA SIMULTANEOUS	NONE
FRONT STROBES ONLY	WHT/BLK	NONE	SAME AS MODE 3
ALL STROBES	BLU & WHT/BLK	DR2, PR2 & DA SIMULTANEOUS AND ALTERNATE WITH RC & PA SIMULTANEOUS	SAME AS MODE 3

CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP
BROWN	FC (TAKEDOWN)
GRAY	DA (DRIVER ALLEY)
YELLOW	PA (PASSENGER ALLEY)

CONTROL WIRES FOR OPTIONAL PRE2-1C PREEMPTION (LOCATION FC)

CONTROL WIRE ACTIVATED	STROBE LAMP
ORG	PRE2-1C ENABLED - PREEMPTION SIGNAL
BRN/WHT	PARKING BRAKE OVERRIDE - PRE2-1C DISABLED

NOTE: GREEN control wire activates high intensity to strobes.
Apply +12vdc to appropriate control wire to activate desired function.