

# 930N-4805-0028 FLASH PATTERN

## LIGHTBAR LAMP CONFIGURATION

DF2	DF1	FC	PF1	PF2
DC				PC
DA				PA
DR2	DR1	RC	PR1	PR2

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR / ALLEY STROBES	FRONT / CORNER STROBES
1 (REAR ONLY)	ORG	DR2 & PR2 SIMULTANEOUS AND ALTERNATE WITH DR1 & PR1 SIMULTANEOUS	NONE
2 (FRONT & ALLEY)	ORG & BLU	DA ALTERNATES WITH PA	DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1 & PF1 SIMULTANEOUS (6 PULSES PER BURST) DC ALTERNATES WITH PC (3 PULSES PER BURST)
3 (360 +)	ORG & BLU & WHT/BLK	DR2, PR2 & DA SIMULTANEOUS AND ALTERNATE WITH DR1, PR1 & PA SIMULTANEOUS	SAME AS MODE 2
RIGHT ARROW	BLU	DR2, DR2 & DR1, DR1 & PR1, PR1 & PR2, PR2, DA & PA, REPEAT	DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1 & PF1 SIMULTANEOUS
LEFT ARROW	WHT/BLK	PR2, PR2 & PR1, PR1 & DR1, DR1 & DR2, DR2, DA & PA, REPEAT	DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1 & PF1 SIMULTANEOUS
CENTER OUT	BLU & WHT/BLK	DR1 & PR1, DR2 & DR1 & PR1 & PR2, DR2 & PR2, DA & PA, REPEAT	DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1 & PF1 SIMULTANEOUS

## CONTROL WIRES FOR OPTIONAL FEATURES

CONTROL WIRE ACTIVATED		LAMP
RED/WHITE	RC	REARWORK or REAR FLASHER or SPLIT WORK or SPLIT FLASHER
BROWN	FC	TAKEDOWN or FRONT FLASHER or SPLIT TAKEDOWN or SPLIT FRONT FLASHER or ( <b>930-PRE2-1C</b> )
GRAY	DA	DRIVER ALLEY
YELLOW	PA	PASSENGER ALLEY

### CONTROL WIRE ( BRN/WHT ) USED FOR ONE OF THE FOLLOWING EXCLUSIVE OPTIONS:

FRONT / CORNER STROBES SEPARATELY – All ON

930-PRE2-1C - PARKING BRAKE OVERRIDE

SPLIT TAKEDOWN or SPLIT FRONT FLASHER in DF1 & PF1

SPLIT REARWORK or SPLIT REAR FLASHER in DR1 & PR1

DUAL MODE applied to TAKEDOWN or SPLIT TAKEDOWN – STEADYBURN / FLASHER

DUAL MODE applied to REARWORK or SPLIT REARWORK – STEADYBURN / FLASHER

DUAL MODE applied to TAKEDOWN & REARWORK – SIMULTANEOUS STEADYBURN / FLASHER

**NOTE: GREEN control wire activates high intensity to strobes.**

**Apply +12vdc to appropriate control wire to activate desired function.**