

# 930N-4805 FLASH PATTERN

## LIGHTBAR LAMP CONFIGURATION

	DF2	DF1	FC	PF1	PF2
DC					PC
DA					PA
	DR2	DR1	RC	PR1	PR2

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR / ALLEY STROBES	FRONT / CORNER STROBES
0	NONE	NONE	NONE
1	ORG (REAR WIG-WAG)	DR1 ALTERNATES WITH PR1	NONE
2	ORG & BLU (360)	DR2, PR2 & DA SIMULTANEOUS AND ALTERNATE WITH DR1, PR1 & PA SIMULTANEOUS	DF1 & PF1 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMULTANEOUS
3	ORG & BLU & WHT/BLK (360 +) With OPTIONAL PRE *PREEMPTION SIGNAL EMITTED	SAME AS MODE 2	DF1 & PF1 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMULTANEOUS (6 PULSES PER BURST) DC ALTERNATES WITH PC (3 PULSES PER BURST)
RIGHT ARROW	BLU	DR2, DR2 & DR1, DR1 & PR1, PR1 & PR2, PR2, DA & PA, REPEAT	SAME AS MODE 2
LEFT ARROW	WHT/BLK	PR2, PR2 & PR1, PR1 & DR1, DR1 & DR2, DR2, DA & PA, REPEAT	SAME AS MODE 2
CENTER OUT	BLU & WHT/BLK	DR1 & PR1, DR2 & DR1 & PR1 & PR2, DR2 & PR2, DA & PA, REPEAT	SAME AS MODE 2

### CONTROL WIRES FOR OPTIONAL HALOGEN LAMPS

CONTROL WIRE ACTIVATED	HALOGEN LAMP
RED/WHITE	RC (REAR WORK)
BROWN	FC (TAKEDOWN)
GRAY	DA (DRIVER ALLEY)
YELLOW	PA (PASSENGER ALLEY)

### CONTROL WIRES FOR OPTIONAL HALOGEN TAKEDOWN / FLASHER

CONTROL WIRE ACTIVATED	HALOGEN LAMP
BROWN	FC (TAKEDOWN FLASHER)
BRN & BRN/WHT**	FC (TAKEDOWN STEADYBURN)

\*\*additional option required

### \*CONTROL WIRES FOR OPTIONAL PREEMPTION EMITTER

CONTROL WIRE ACTIVATED	PARKING BRAKE OVERRIDE
BRN/WHT	

Activation will change the flash rate from PREEMPTION to standard NEOBE™.  
\* Preemption and Flasher w/ override Steadyburn can not be ordered at the same time.

**NOTE: GREEN control wire activates high intensity to strobes.**  
**Apply +12vdc to appropriate control wire to activate desired function.**  
**Cut loop (22 AWG BLACK) on 930F (FRONT power supply) to disable FRONT strobes during traffic direction modes – Not available on PRE Option.**