

# 930N-5606-0013/STT FLASH PATTERN

## LIGHTBAR LAMP CONFIGURATION

DF3	DF2	DF1	PF1	PF2	PF3
DC					PC
DA					PA
DR3	DR2	DR1	PR1	PR2	PR3

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR / ALLEY STROBES	FRONT / CORNER STROBES
0	NONE	NONE	NONE
1	ORG	DR3 ALTERNATES WITH PR3 (6 PULSES PER BURST)	DF3 ALTERNATES WITH PF3 (6 PULSES PER BURST) DC ALTERNATES WITH PC (3 PULSES PER BURST)

## CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP
RED/WHITE	DF1 (WORK LIGHT)
BROWN	PF1 (WORK LIGHT)
BROWN/WHITE	DF2 & PF2 (TAIL LIGHTS)
GRAY	DF2 (TURN SIGNAL)
YELLOW	PF2 (TURN SIGNAL)

## CONTROL WIRES FOR OPTIONAL DUAL MODE FLASHER

CONTROL WIRE ACTIVATED	HALOGEN LAMP
BLUE	DR1 & PR1 (FLASHER MODE)
WHT/BLK or BLU & WHT/BLK	DR1 & PR1 (STEADYBURN MODE)

**NOTE: GREEN control wire activates high intensity to strobes.  
Apply +12vdc to appropriate control wire to activate desired function.**