930N-8810-0039 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF5 DF4 DF3 DF2 DF1 PF1 PF2 PF3 PF4 PF5
DC PC
DA PA
DR5 DR4 DR3 DR2 DR1 PR1 PR2 PR3 PR4 PR5

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR STROBES	FRONT / CORNER / ALLEY STROBES
1	ORG (FRONT ONLY)	NONE	PF1 & PF4 SIMULTANEOUS AND ALTERNATE WITH PF2 & PF5 SIMULTANEOUS PC ALTERNATES PA PF3 (3 PULSES PER BURST) DF1 & DF5 SIMULTANEOUS AND ALTERNATE WITH DF2 & DF4 SIMULTANEOUS DC ALTERNATES WITH DA DF3 (3 PULSES PER BURST)
2	ORG & BLU (REAR ONLY)	DR4 & PR4 SIMULTANEOUS AND ALTERNATE WITH DR2 & PR2 SIMULTANEOUS DR1 ALTERNATES WITH PR1 DR3 ALTERNATES WITH PR3	NONE
3	ORG & BLU & WHT/BLK (ALL STROBES)	SAME AS MODE 2	SAME AS MODE 1
4	BLU (RIGHT ARROW)	DR4, DR4 & DR3, DR3 & DR2, DR2 & DR1, DR1 & PR1, PR1 & PR2, PR2 & PR3, PR3 & PR4, PR4, REPEAT	NONE
5	WHT/BLK (LEFT ARROW)	PR4, PR4 & PR3, PR3 & PR2, PR2 & PR1, PR1 & DR1, DR1 & DR2, DR2 & DR3, DR3 & DR4, DR4, REPEAT	NONE
6	BLU & WHT/BLK (CENTER OUT)	DR1 & PR1, DR2 & DR1 & PR1 & PR2, DR3 & DR2 & PR2 & PR3, DR4 & DR3 & PR3 & PR4, DR4 & PR4, REPEAT	NONE

CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP	
BRN	DR5	(REAR WORK)
RED/WHT	PR5	(REAR WORK)
GRY	DA	(DRIVER ALLEY)
YEL	PA	(PASSENGER ALLEY)
BRN/WHT	DF1 & PF1	(SPLIT TAKEDOWN)

NOTE: GREEN control wire activates high intensity to strobes.
Apply +12vdc to appropriate control wire to activate desired function.