930N1-7208-PS03 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF4 DF3 DF2 DF1 PF1 PF2 PF3 PF4
DC PC
DA PA
DR4 DR3 DR2 DR1 PR1 PR2 PR3 PR4

FLASH PATTERN: NFPA-1901 TOMAR PUMPER SYSTEM 3

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		FRONT / CORNER / ALLEY STROBES	ALLEY HALOGENS
1	BLUE (BLOCKING THE RIGHT OF WAY)	DF4, DA & PC SIMULTANEOUS AND ALTERNATE WITH PF4, PA & DC SIMULTANEOUS (6 PULSES PER BURST) DF3 & PF3 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMULTANEOUS (6 PULSES PER BURST)	DA ALTERNATES WITH PA
2	ORANGE & BLUE (CLEARING THE RIGHT OF WAY)	DF4, DA & PC SIMULTANEOUS AND ALTERNATE WITH PF4, PA & DC SIMULTANEOUS (6 PULSES PER BURST) DF3 & PF3 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMULTANEOUS (6 PULSES PER BURST) DF1 ALTERNATES WITH PF1 (3 PULSES PER BURST)	DA ALTERNATES WITH PA

OPTIONAL 930-PRE PREEMPTION EMITTER

Forward facing strobes will emit a High or Low priority preemption signal

C.R.O.W.	**PREEMPTION SIGNAL EMITTED**
C.R.O.W. + WHT/BLK	Standard NEOBE® Flash Rate

When ordering a Preemption system, please specify High or Low priority for factory configuration

NOTE:

1. **The 930N-7208-PS03 Light Bar is factory wired for High Intensity operation to meet NFPA specifications.**
2. **Apply +12vdc to appropriate control wire to activate desired function.**