930N1-8009-PS03 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF4 DF3 DF2 DF1 FC PF1 PF2 PF3 PF4
DC PC
DA PA
DR4 DR3 DR2 DR1 RC PR1 PR2 PR3 PR4

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		FRONT / CORNER / ALLEY STROBES	FRONT / ALLEY HALOGENS
1	ORANGE & BLUE (CLEARING THE RIGHT OF WAY)	DF4, DA & PC SIMULTANEOUS AND ALTERNATE WITH PF4, PA & DC SIMULTANEOUS (6 PULSES PER BURST) DF3 & PF3 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMULTANEOUS (6 PULSES PER BURST) DF1 ALTERNATES WITH PF1 (3 PULSES PER BURST)	DA ALTERNATES WITH PA FC - OPTIONAL ALTERNATING HALOGEN FLASHER OR STEADY BURN HALOGEN
2	BLUE (BLOCKING THE RIGHT OF WAY)	DF4, DA & PC SIMULTANEOUS AND ALTERNATE WITH PF4, PA & DC SIMULTANEOUS (6 PULSES PER BURST) DF3 & PF3 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMULTANEOUS (6 PULSES PER BURST)	DA ALTERNATES WITH PA

OPTIONAL 930-PRE PREEMPTION EMITTER

Forward facing strobes will emit a High or Low priority preemption signal

C.R.O.W.	**PREEMPTION SIGNAL EMITTED**
C.R.O.W. + WHT/BLK	Standard NEOBE® Flash Rate

OPTIONAL 930-PRE2-1C SINGLE HEAD PREEMPTION EMITTER

FC strobe will emit a High or Low priority preemption signal

C.R.O.W.	Standard NEOBE® Flash Rate
C.R.O.W. + WHT/BLK	**PREEMPTION SIGNAL EMITTED**

OPTIONAL FC HALOGEN FLASHER

THE OPTIONAL FC HALOGEN LAMP MUST BE AN NFPA 'ZONE A' PERMISSIBLE COLOR; CLEAR, BLUE OR RED. IF FC IS CLEAR, THE LAMP WILL DISABLED IN THE CLEARING THE RIGHT OF WAY MODE.

NOTE:

1. **The 930N1-8009-PS03 Light Bar is factory wired for High Intensity operation to meet NFPA specifications.**

   Apply +12vdc to appropriate control wire to activate desired function.