

4X 6-32 THD  
OR CLEARANCE FOR 6-32 SCREWS  
RECOMMENDED Ø .156" (Ø 5/32") THRU

REF 9.125" (9 1/8") LAMP OUTLINE

7.25" (7 1/4")

2X Ø1.125" (Ø 1 1/8") MIN THRU  
WP CONNECTOR VERSION  
REQUIRED REAR CLEARANCE .875" (7/8") MIN


REF 7.125" (7 1/8") LAMP OUTLINE

5.25" (5 1/4")

3.120"

2X Ø.375" (Ø 3/8") MIN THRU  
WIRE VERSION

4.577"

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES: DECIMALS .XX + ____ - ____ .XXX + ____ - ____ ANGLES ± ____ - ____ SCALE 1/1 DO NOT SCALE DRAWING DRAWN AML 09/02/04 APPROVED _____ © COPYRIGHT 2003 TOMAR ELECTRONICS INC.	REV	DATE	DESCRIPTION	TOMAR ELECTRONICS INC. 2100 WEST OBISPO GILBERT, ARIZONA 85233	
	01	04/08/05	ADD WIRE/WP		
				DRILL TEMPLATE - RECT-79L	DRAWING NO. REV 13633 01
				TOMAR PART NO: FP _____ PC _____ TE _____	SHT 1 OF 1