

4X 6-32 THD  
OR CLEARANCE FOR 6-32 SCREWS  
RECOMMENDED Ø .156" (Ø 5/32") THRU

REF 7.25" (7 1/4") LAMP OUTLINE

6.556"


Ø1.125 (Ø 1 1/8") MIN THRU  
WP CONNECTOR VERSION  
REQUIRED REAR CLEARANCE .875" (7/8") MIN

REF 3.00" LAMP OUTLINE

2.376"

Ø.375 (Ø 3/8") MIN THRU  
WIRE VERSION

4.577"

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES: DECIMALS .XX + ____ - ____ .XXX + ____ - ____ ANGLES ± ____ SCALE 1/1 DO NOT SCALE DRAWING DRAWN AML 09/02/04 APPROVED _____ © COPYRIGHT 2003 TOMAR ELECTRONICS INC.	REV	DATE	DESCRIPTION	TOMAR ELECTRONICS INC. 2100 WEST OBISPO GILBERT, ARIZONA 85233	
				DRILL TEMPLATE - RECT-37L	
				TOMAR PART NO:	13634 00
				FP _____ PC _____ TE _____	SHT 1 OF 1