

## MODEL 1100-250 POWER ALARM 250 VDC $\pm$ 20% INSTALLATION AND OPERATING INSTRUCTIONS

### **INSTALLATION**

The Power Alarm is a solid state electronic siren with field adjustable volume and tone selection. The Power Alarm has been designed to operate from ungrounded or grounded industrial 250 VDC Power Systems.

The separately purchased model 1001 speaker may be mounted remotely from the Power Alarm base. The installer should connect the speaker to the Power Alarm with #14 AWG wire minimum to obtain full performance. Wiring length should be limited to 200 feet. Longer wire lengths require increased wire gauge.

The Power Alarm metal cabinet must be grounded and may be mounted in either a horizontal or vertical orientation.

### **OPERATION**

Apply power to activate the Power Alarm.

Caution: The 1100-250 control logic has 250 VDC potential on case. Use an insulated screwdriver when adjusting volume or selecting sound tones.

### **SPECIFICATIONS**

Operating Voltage: 180 VDC or 300 VDC, 250 VDC Nominal  
Input Current: 0.25 Amp @ 250 VDC  
Output: 116db. Sound Pressure Level at 10 feet  
Output Impedance: 8 Ohms  
Output Protection: The output is fully protected for shorts or opens in the speaker wiring.

### **SERVICE AND REPAIR**

Please contact the factory for service or repair.

**TOMAR** Electronics, Inc.

2100 West Obispo  
Gilbert, Arizona 85233  
(480) 497-4400 (800) 338-3133  
FAX (480) 497-4416 (800) 688-6627  
E-mail: sales@tomar.com www.tomar.com