930NH-4805-0004 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF2 DF1 FC PF1 PF2
DC PC
DA PA
DR2 DR1 RCL/RCR PR1 PR2

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR / ALLEY STROBES & HALOGENS	FRONT / CORNER STROBES & HALOGENS
1	ORG	DR2 ALTERNATES WITH PR2 *RCL ALTERNATES WITH *RCR	NONE
2	ORG & BLU	DR2 & DR1 SIMULTANEOUS AND ALTERNATE WITH PR2 & PR1 SIMULTANEOUS *RCL ALTERNATES WITH *RCR DA ALTERNATES WITH PA	DF2 & DF1 SIMULTANEOUS AND ALTERNATE WITH PF2 & PF1 SIMULTANEOUS
3	ORG & BLU & WHT/BLK	SAME AS MODE 2	DF2 & DF1 SIMULTANEOUS AND ALTERNATE WITH PF2 & PF1 SIMULTANEOUS DC ALTERNATES WITH PC
STROBES ONLY	BLU	DR2 ALTERNATES WITH PR2 (6 PULSES PER BURST)	DF2 ALTERNATES WITH PF2 (6 PULSES PER BURST) DC ALTERNATES WITH PC (3 PULSES PER BURST)
HALOGENS ONLY (MODE 1)	WHT/BLK	DR1 ALTERNATES WITH PR1	NONE
HALOGENS ONLY (MODE 2)	ORG & WHT/BLK	DR1 ALTERNATES WITH PR1 *RCL ALTERNATES WITH *RCR DA ALTERNATES WITH PA	DF1 ALTERNATES WITH PF1

* OPTIONAL SYNCHRONIZED REAR FLASHER

CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP	
BROWN	FC	TAKEDOWN or FRONT FLASHER
GRAY	DA	DRIVER ALLEY
YELLOW	PA	PASSENGER ALLEY
RED/WHT	RC	REAR WORK or INDEPENDENT REAR FLASHER
BROWN/WHITE	DF1	CA STEADY RED

CONTROL WIRE FOR OPTIONAL PRE2-1C PREEMPTION EMITTER

CONTROL WIRE ACTIVATED	STROBE LAMP
BROWN/WHITE	FC

NOTE: GREEN control wire activates high intensity to strobes.
Apply +12vdc to appropriate control wire to activate desired function.