

# 930NH-4004 FLASH PATTERN

## LIGHTBAR LAMP CONFIGURATION

	DF2	DF1	PF1	PF2	
DC					PC
DA					PA
	DR2	DR1	PR1	PR2	

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR / ALLEY STROBES & HALOGENS	FRONT / CORNER STROBES & HALOGENS
1	ORG	DR2 & DR1 SIMULTANEOUS AND ALTERNATE WITH PR2 & PR1 SIMULTANEOUS	NONE
2	ORG & BLU	DR2 & DR1 SIMULTANEOUS AND ALTERNATE WITH PR2 & PR1 SIMULTANEOUS DA ALTERNATES WITH PA	DF2 & DF1 SIMULTANEOUS AND ALTERNATE WITH PF2 & PF1 SIMULTANEOUS
3	ORG & BLU & WHT/BLK	SAME AS MODE 2	DF2, DF1 SIMULTANEOUS AND ALTERNATE WITH PF2, PF1 SIMULTANEOUS DC ALTERNATES WITH PC
4	BLU (STROBES ONLY)	DR2 ALTERNATE WITH PR2	DF2 ALTERNATES WITH PF2 DC ALTERNATES WITH PC
5	WHT/BLK (HALOGENS ONLY MODE 1)	DR1 ALTERNATES WITH PR1	NONE
6	ORG & WHT/BLK (HALOGENS ONLY MODE 2)	DR1 ALTRNATES WITH PR1 DA ALTERNATES WITH PA	DF1 ALTERNATE WITH PF1

## CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP	
RED/WHT	DR1R & PR1L	(REAR WORK)
BROWN	DF1R & PF1L	(TAKEDOWN)
GRAY	DA	(DRIVER ALLEY)
YELLOW	PA	(PASSENGER ALLEY)

**NOTE: GREEN control wire activates high intensity to strobes.  
Apply +12vdc to appropriate control wire to activate desired function.**