

# **465H-6407 FLASH PATTERN**

## **LIGHTBAR LAMP CONFIGURATION**

DC            DF3    DF2    DF1    FC        PF1    PF2    PF3                            PC

MODE	CONTROL WIRES ACTIVATED	HALOGEN LAMP OPERATION
1	RED/WHT	DF1*, PF1*, DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DC, DF3, PF3 & PC SIMULTANEOUS

\* Note: **OPTIONAL SYNCHRONIZED HALOGENS** – Up to 4 Halogen bulbs may be designated 'synchronized' out of 6 potential Halogen Lamp positions in DF1, FC & PF1 locations.

### **CONTROL WIRES FOR OPTIONAL HALOGEN**

CONTROL WIRE ACTIVATED	OPERATION
BRN	FC    TAKEDOWN
YEL	PF1   SOLID or SPLIT TAKEDOWN
GRY	DF1   SOLID or SPLIT TAKEDOWN

### **CONTROL WIRES FOR OPTIONAL PRE2-1C**

CONTROL WIRE ACTIVATED	FC STROBE LAMP
BRN/WHT	ACTIVATE PREEMPTION EMITTER

**NOTE: GREEN control wire activates high intensity to strobes.  
 Apply +12vdc to appropriate control wire to activate desired function.**