

930NH1-5606 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF3	DF2	DF1	PF1	PF2	PF3
DC					PC
DA					PA
DR3	DR2	DR1	PR1	PR2	PR3

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		HALOGENS	STROBES
0	NONE	NONE	NONE
1	ORG	NONE	DF1 ALTERNATES WITH PF1
2	ORG & BLU	DF2 ALTERNATE WITH PF2	DF1, DF3 & PA SIMULTANEOUS AND ALTERNATE WITH PF1, PF3 & DA SIMULTANEOUS
3	ORG & BLU & WHT/BLK	DF2 & DC ALTERNATE WITH PF2 & PC	SAME AS MODE 2
4	BLU (STROBES ONLY)	NONE	SAME AS MODE 2
5	ORG & WHT/BLK (HALOGENS ONLY)	SAME AS MODE 3	NONE

NOTE: Halogen lamps DF2, PF2 each have 2 halogen bulbs per lamp. And as indicated above, the Standard flash pattern specifies both bulbs in DF2 flash at the same time and alternate with PF2 (both bulbs flashing at the same time).

The 930NH1-5606 Lightbar may also be ordered from the factory with the 930-HSPLIT-18 Option, in which case the 1st halogen bulb in each DF2 & PF2 will alternate with 2nd halogen bulb in the same lamp.

CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP
BROWN	DF1 & PF1 (SPLIT TAKEDOWN)
GRAY	DA (DRIVER ALLEY)
YELLOW	PA (PASSENGER ALLEY)

NOTE: GREEN control wire activates high intensity to strobes.

Apply +12vdc to appropriate control wire to activate desired function.