

465NH-6407-0098 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF3 DF2 DF1 FC PF1 PF2 PF3
DC PC

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION
		FRONT / CORNER STROBES & HALOGENS
1	RED/WHT (HALOGENS ONLY)	DF1, PF1, DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF3 & PF3 SIMULTANEOUS
2	ORG (STROBES ONLY)	DC & PC SIMULTANEOUS AND ALTERNATE WITH FC
3	ORG & RED/WHT 'ALL ON'	DF1, PF1, DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF3 & PF3 SIMULTANEOUS DC & PC SIMULTANEOUS AND ALTERNATE WITH FC

CONTROL WIRE FOR OPTIONAL SPLIT TAKEDOWN HALOGENS

CONTROL WIRE ACTIVATED
BRN

HALOGEN LAMP
DF1 & PF1 SPLIT TAKEDOWN

**NOTE: GREEN control wire activates high intensity to strobes.
Apply +12vdc to appropriate control wire to activate desired function.**