

# 930NH-4805-0125 FLASH PATTERN

## LIGHTBAR LAMP CONFIGURATION

DF2	DF1	FC	PF1	PF2
DC				PC
DA				PA
DR2	DR1	RC	PR1	PR2

CONTROL WIRES ACTIVATED	LAMP OPERATION	
	HALOGEN & LED	STROBES
ORG <b>HALOGEN &amp; LED ONLY</b>	DF1, PF1, <b>DA-A &amp; PA-A</b> SIMULTANEOUS AND ALTERNATE DF2, PF2, DR1, PR1, DAF & PAF	NONE
BRN/WHT & BRN <b>REAR STROBES</b>	NONE	DR2 & PR2 SIMULTANEOUS AND ALTERNATE WITH RCR & RCL SIMULTANEOUS
RED/WHT <b>FRONT STROBES</b>	NONE	FCL & FCR SIMULTANEOUS AND ALTERNATE WITH DC & PC SIMULTANEOUS

## CONTROL WIRES FOR STEADYBURN SPLIT ALLEY HALOGENS

<b>CONTROL WIRE ACTIVATED</b>	<b>HALOGEN LAMP</b>	
GRN	<b>DA-A</b>	DRIVER ALLEY
WHT/BLK	<b>PA-A</b>	PASSENGER ALLEY

**NOTE: GREEN control wire activates high intensity to strobes.  
Apply +12vdc to appropriate control wire to activate desired function.**